



# LED LIGHT TUBE SERIES

www.sotac.com.tw

## T5 LED Tube ( Aluminum + Plastic Dimmable)

Rated Voltage: 100-127V 60HZ  
 Color Temperature: 3000K, 4000K, 6500K  
 Average Lifetime: 35000h  
 Color Rendering Index(TYPE): 80  
 UV and IR free, Mercury free  
 Suitable for indoor use  
 RoHS compliant



Model Number	Watt(W)	Lumen	Base	Beam Angle	M.O.D mm/inch	M.O.L mm/inch	Remark
		3000K-6500K					
K-T5D60	10	800	G5	110	18/0.71	548/21.5	dimmble
K-T5D120	20	1750					

Product specifications subjects to change without prior notice.

## T5 LED Batten (AC100-240V ,Non-Dim)

Rated Voltage: 100-240V  
 Color Temperature: 3000K, 4000K, 6500K  
 Average Lifetime: 35000h  
 Color Rendering Index(TYPE): 80  
 UV and IR free, Mercury free  
 Suitable for indoor use  
 RoHS compliant



Model Number	Watt(W)	Lumen	Base	Beam Angle	M.O.D mm/inch	M.O.L mm/inch	Remark
		3000K-6500K					
K-T51J-30A K-T51J-65A	3.5	350	G5	110	22.2/0.88	315/12.40	Non-dimmble
	5	400					
K-T52J-30A K-T52J-65A	7	700	G5	110	22.2/0.88	575/22.64	Non-dimmble
	9	800					
K-T53J-30A K-T53J-65A	10	1000	G5	110	22.2/0.88	875/34.45	Non-dimmble
	11	1100					
K-T54J-30A K-T54J-65A	13	1150	G5	110	22.2/0.88	1024/40.32	Non-dimmble
	14	1250					
K-T55J-30A K-T55J-65A	14	1400	G5	110	22.2/0.88	1175/46.26	Non-dimmble
	18	1600					

Product specifications subjects to change without prior notice.

## T5 LED Tube (AC100-240V ,Non-Dim)

Rated Voltage: 100-240V  
 Color Temperature: 3000K, 4000K, 6500K  
 Average Lifetime: 35000h  
 Color Rendering Index(TYPE): 80  
 UV and IR free, Mercury free  
 Suitable for indoor use  
 RoHS compliant



Model Number	Watt(W)	Lumen	Base	Beam Angle	M.O.D mm/inch	M.O.L mm/inch	Remark
		3000K-6500K					
K-T52C	9	900	G5	110	18/0.71	549/21.62	Non-dimble
K-T54C	18	1800			18/0.71	1149/45.24	

Product specifications subjects to change without prior notice.

## T8 LED Tube ( Aluminum + Plastic )

Rated Voltage: AC100-277V  
 Color Temperature: 2700K, 3000K, 4000K, 6500K  
 Average Lifetime: 25000h  
 Color Rendering Index(TYPE): 80  
 UV and IR free, Mercury free  
 Suitable for indoor use  
 RoHS compliant



Model Number	Watt(W)	Lumen	Base	Beam Angle	M.O.D mm/inch	M.O.L mm/inch	Remark
		3000K-6500K					
K-T82F10CW	10	1150	G13	120	26/1.03	589/23.19	UL
K-T84F16CW	16	1840			26/1.03	1198/47.17	
K-T84F22CW	22	2530			26/1.03	1198/47.17	

Product specifications subjects to change without prior notice.

## T6 LED Tube (AC100-240V ,Non-Dim)

Rated Voltage: 100-240V  
 Color Temperature: 3000K,4000K, 6500K  
 Average Lifetime: 35000h  
 Color Rendering Index(TYPE): 80  
 UV and IR free, Mercury free  
 Suitable for indoor use  
 RoHS compliant



Model Number	Watt(W)	Lumen	Base	Beam Angle	M.O.D mm/inch	M.O.L mm/inch	Remark
		3000K-6500K					
K-T62H-09-65A/30A	9	800	G5	110	22.2/0.88	549/21.62	Non-dimble
K-T62H-09-65A/30A	16	1600			22.2/0.88	1149/45.24	

Product specifications subjects to change without prior notice.

## T8 LED Tube ( Aluminum + Plastic ) (Electronic ballast compatible)

Rated Voltage: AC100-277V  
 Color Temperature: 2700K, 3000K, 4000K, 6500K  
 Average Lifetime: 25000h  
 Color Rendering Index(TYPE): 80  
 UV and IR free, Mercury free  
 Suitable for indoor use  
 RoHS compliant



Model Number	Watt(W)	Lumen	Base	Beam Angle	M.O.D mm/inch	M.O.L mm/inch	Remark
		3000K-6500K					
K-U608-2F10W	10	1150	G13	120	26/1.03	589/23.19	UL
K-U608-4F18W	18	2070			26/1.03	1198/47.17	

Product specifications subjects to change without prior notice.

**T8 LED Tube ( Glass + Plastic )**

Rated Voltage: AC100-277V  
 Color Temperature: 2700K, 3000K, 4000K, 6500K  
 Average Lifetime: 25000h  
 Color Rendering Index(TYPE): 80  
 UV and IR free, Mercury free  
 Suitable for indoor use  
 RoHS compliant



Model Number	Watt(W)	Lumen		Base	Beam Angle	M.O.D mm/inch	M.O.L mm/inch	Remark
		3000K	4000K					
K09-W830G1306	9	900	1000	G13	300	26/1.03	589/23.19	UL/DLC
K18-W830G1312	18	1800	2000			26/1.03	1198/47.17	

Product specifications subjects to change without prior notice.

**T8 LED Tube ( Glass + Plastic )  
( DLC electronic ballast compatible )**

Rated Voltage: AC100-277V  
 Color Temperature: 2700K, 3000K, 4000K, 6500K  
 Average Lifetime: 25000h  
 Color Rendering Index(TYPE): 80  
 UV and IR free, Mercury free  
 Suitable for indoor use  
 RoHS compliant



Model Number	Watt(W)	Lumen		Base	Beam Angle	M.O.D mm/inch	M.O.L mm/inch	Remark
		3000K	4000K					
K09-W840G1306	9	900	1000	G13	300	26/1.03	589/23.19	UL/DLC
K18-W840G1312	18	1800	2000			26/1.03	1198/47.17	

Product specifications subjects to change without prior notice.

**T8 LED Tube ( Nanotube )**

Rated Voltage: AC100-277V  
 Color Temperature: 2700K, 3000K, 4000K, 6500K  
 Average Lifetime: 25000h  
 Color Rendering Index(TYPE): 80  
 UV and IR free, Mercury free  
 Suitable for indoor use  
 RoHS compliant



Model Number	Watt(W)	Lumen	Base	Beam Angle	M.O.D mm/inch	M.O.L mm/inch	Remark
		2700K-6500K					
K-N4T8VHO-18W	18	1900	G13	300	26/1.03	589/23.19	UL/DLC
K-N4T8VHOH-18W	18	2200			26/1.03	1198/47.17	

Product specifications subjects to change without prior notice.

**T8 LED Tube ( Nanotube )  
( Electronic ballast compatible )**

Rated Voltage: AC100-277V  
 Color Temperature: 2700K, 3000K, 4000K, 6500K  
 Average Lifetime: 25000h  
 Color Rendering Index(TYPE): 80  
 UV and IR free, Mercury free  
 Suitable for indoor use  
 RoHS compliant



Model Number	Watt(W)	Lumen	Base	Beam Angle	M.O.D mm/inch	M.O.L mm/inch	Remark
		2700K-6500K					
K-N4T8DF-18W	18	1800	G13	300	26/1.03	1198/47.17	UL/DLC
K-N4T8DFG-18W	18	2200			26/1.03	1198/47.17	
K-N4T8DFH-18W	18	2500			26/1.03	1198/47.17	

Product specifications subjects to change without prior notice.

**T8 LED Tube ( Nanotube )  
( AC electronic ballast compatible )**

Rated Voltage: AC100-277V  
 Color Temperature: 2700K, 3000K, 4000K, 6500K  
 Average Lifetime: 25000h  
 Color Rendering Index(TYPE): 80  
 UV and IR free, Mercury free  
 Suitable for indoor use  
 RoHS compliant



Model Number	Watt(W)	Lumen	Base	Beam Angle	M.O.D mm/inch	M.O.L mm/inch	Remark
		2700K-6500K					
K-N4T8DF-18W-DUO	18	1800	G13	300	26/1.03	1198/47.17	UL/DLC
K-N4T8DFG-18W-DUO	18	2200			26/1.03	1198/47.17	
K-N4T8DFH-18W-DUO	18	2500			26/1.03	1198/47.17	

Product specifications subjects to change without prior notice.